

Geometry of image formation

Tomáš Svoboda, svoboda@cmp.felk.cvut.cz

Czech Technical University in Prague, Center for Machine Perception

<http://cmp.felk.cvut.cz>

Last update: July 4, 2008

Talk Outline

- ◆ Pinhole model
- ◆ Camera parameters
- ◆ Estimation of the parameters—Camera calibration


Motivation

- ◆ parallel lines
- ◆ window sizes
- ◆ image units
- ◆ distance from the camera




What will we learn

- ◆ how does the 3D world project to 2D image plane?
- ◆ how is a camera modeled?
- ◆ how can we estimate the camera model?




Pinhole camera



1

¹http://en.wikipedia.org/wiki/Pinhole_camera

Camera Obscura



2

²http://en.wikipedia.org/wiki/Camera_obscura


Camera Obscura — room-sized




Used by the art department at the UNC at Chapel Hill

³http://en.wikipedia.org/wiki/Camera_obscura

1D Pinhole camera



1D Pinhole camera projects 2D to 1D




optical axis


$$\frac{x_1}{-f} = \frac{X_1}{Z_1}$$

$$x_1 = -f \frac{X_1}{Z_1}$$


Problems with perspective I



Problems with perspective II




Get rid of the $(-)$ sign





How does the 3D world
project to the 2D image plane?


A 3D point \mathbf{X} in a world coordinate system




A pinhole camera observes a scene




Point **X** projects to the image plane, point **x**





Scene projection



Scene projection



3D Scene projection – observations



- ◆ 3D lines project to 2D lines
- ◆ but the angles change, parallel lines are no more parallel.
- ◆ area ratios change, note the front and backside of the house

Put the sketches into equations

3D → 2D Projection

We remember that: $\mathbf{x} = \left[\frac{fX}{Z}, \frac{fY}{Z} \right]^\top$


$$\begin{bmatrix} \mathbf{x} \\ 1 \end{bmatrix} \approx \begin{bmatrix} fX \\ fY \\ Z \end{bmatrix}$$

$$\begin{bmatrix} \mathbf{x} \\ 1 \end{bmatrix} \approx \begin{bmatrix} f & 0 & 0 \\ f & 0 & 0 \\ 1 & 0 & 0 \end{bmatrix} \begin{bmatrix} \mathbf{x} \\ 1 \end{bmatrix}$$

Use the homogeneous coordinates⁴

$$\lambda_{[1 \times 1]} \mathbf{x}_{[3 \times 1]} = K_{[3 \times 3]} \left[\begin{array}{c|cc} \mathbf{I} & \mathbf{0} \end{array} \right] \mathbf{X}_{[4 \times 1]}$$

but . . .



⁴for the notation conventions, see the talk notes

. . . we need the \mathbf{X} in camera coordinate system

Rotate the vector:

$$\mathbf{X} = \mathbf{R}(\mathbf{X}_w - \mathbf{C}_w)$$


\mathbf{R} is a 3×3 rotation matrix. The point coordinates \mathbf{X} are now in the camera frame.

Use homogeneous coordinates to get a matrix equation

$$\begin{bmatrix} \mathbf{X} \\ 1 \end{bmatrix} = \begin{bmatrix} \mathbf{R} & -\mathbf{R}\mathbf{C}_w \\ \mathbf{0} & 1 \end{bmatrix} \begin{bmatrix} \mathbf{X}_w \\ 1 \end{bmatrix}$$

The camera center \mathbf{C}_w is often replaced by the translation vector

$$\mathbf{t} = -\mathbf{R}\mathbf{C}_w$$




External (extrinsic parameters)

The translation vector \mathbf{t} and the rotation matrix \mathbf{R} are called **External** parameters of the camera.


$$\mathbf{x} \simeq K [I | \mathbf{0}] \begin{bmatrix} \mathbf{X} \\ 1 \end{bmatrix}$$

$$\lambda \mathbf{x} = K [\mathbf{R} \quad \mathbf{t}] \begin{bmatrix} \mathbf{X}_w \\ 1 \end{bmatrix}$$

Camera parameters (so far): $f, \mathbf{R}, \mathbf{t}$
 Is it all? What can we model?







What is the geometry good for?



video: Zoom out vs. motion away from scene

- ◆ How would you characterize the difference?
- ◆ Would you guess the motion type?

What is the geometry good for?




<http://visionbook.felk.cvut.cz>

video: Zoom out vs. motion away from scene

Enough geometry⁵, look at **real** images

⁵just for a moment


From geometry to pixels and back again




Problems with pixels



Is this a straight line?



Problems with pixels






m p

30/47

What are we looking at?









m p

31/47

Did you recognize it?



Pixel images revisited



- ◆ There are **no** negative coordinates. Where is the principal point?
- ◆ Lines are not lines any more.
- ◆ Pixels, considered independently, do not carry much information.



Pixel coordinate system

Assume normalized geometrical coordinates $\mathbf{x} = [x, y, 1]^\top$

$$u = m_u(-x) + u_0$$

$$v = m_v y + v_0$$

where m_u, m_v are sizes of the pixels and $[u_0, v_0]^\top$ are coordinates of the principal point.



Put pixels and geometry together

From 3D to image coordinates:

$$\begin{bmatrix} \lambda x \\ \lambda y \\ \lambda \end{bmatrix} = \begin{bmatrix} f & 0 & 0 \\ 0 & f & 0 \\ 0 & 0 & 1 \end{bmatrix} \begin{bmatrix} R & t \end{bmatrix} \mathbf{X}_{[4 \times 1]}$$

From normalized coordinates to pixels:

$$\begin{bmatrix} u \\ v \\ 1 \end{bmatrix} = \begin{bmatrix} -m_u & 0 & u_0 \\ 0 & m_v & v_0 \\ 0 & 0 & 1 \end{bmatrix} \begin{bmatrix} x \\ y \\ 1 \end{bmatrix}$$

Put them together:

$$\frac{1}{\lambda} \begin{bmatrix} u \\ v \\ 1 \end{bmatrix} = \begin{bmatrix} -fm_u & 0 & u_0 \\ 0 & fm_v & v_0 \\ 0 & 0 & 1 \end{bmatrix} \begin{bmatrix} R & t \end{bmatrix} \mathbf{X}$$

Finally:

$$\mathbf{u} \simeq K \begin{bmatrix} R & t \end{bmatrix} \mathbf{X}$$

Introducing a 3×4 camera projection matrix P :

$$\mathbf{u} \simeq P \mathbf{X}$$

Non-linear distortion

Several models exist. Less standardized than the linear model. We will consider a simple one-parameter radial distortion. \mathbf{x}_n denote the linear image coordinates, \mathbf{x}_d the distorted ones.

$$\mathbf{x}_d = (1 + \kappa r^2) \mathbf{x}_n$$

where κ is the distortion parameter, and $r^2 = x_n^2 + y_n^2$ is the distance from the principal point.

Observable are the distorted pixel coordinates

$$\mathbf{u}_d = \mathbf{K} \mathbf{x}_d$$

Assume that we know κ . How to get the lines back?

Undoing Radial Distortion

From pixels to distorted image coordinates: $\mathbf{x}_d = \mathbf{K}^{-1}\mathbf{u}_d$

From distorted to linear image coordinates: $\mathbf{x}_n = \frac{\mathbf{x}_d}{1+\kappa r^2}$

Where is the problem? $r^2 = x_n^2 + y_n^2$. We have unknowns on both sides of the equation.

Iterative solution:

1. initialize $\mathbf{x}_n = \mathbf{x}_d$
2. $r^2 = x_n^2 + y_n^2$
3. compute $\mathbf{x}_n = \frac{\mathbf{x}_d}{1+\kappa r^2}$
4. go to 2. (and repeat few times)

And back to pixels $\mathbf{u}_n = \mathbf{K}\mathbf{x}_n$

Undoing Radial Distortion



video

Estimation of camera parameters—camera calibration

The goal: estimate the 3×4 camera projection matrix \mathbf{P} and possibly the parameters of the non-linear distortion κ from images.

Assume a known projection $[u, v]^\top$ of a 3D point \mathbf{X} with known coordinates

$$\begin{bmatrix} \lambda u \\ \lambda v \\ \lambda \end{bmatrix} = \begin{bmatrix} \mathbf{P}_1^\top \\ \mathbf{P}_2^\top \\ \mathbf{P}_3^\top \end{bmatrix} \begin{bmatrix} X \\ Y \\ Z \\ 1 \end{bmatrix}$$

$$\frac{\lambda u}{\lambda} = \frac{\mathbf{P}_1^\top \mathbf{X}}{\mathbf{P}_3^\top \mathbf{X}} \quad \text{and} \quad \frac{\lambda v}{\lambda} = \frac{\mathbf{P}_2^\top \mathbf{X}}{\mathbf{P}_3^\top \mathbf{X}}$$

Re-arrange and assume⁶ $\lambda \neq 0$ to get set of homogeneous equations

$$\begin{aligned} u \mathbf{X}^\top \mathbf{P}_3 - \mathbf{X}^\top \mathbf{P}_1 &= 0 \\ v \mathbf{X}^\top \mathbf{P}_3 - \mathbf{X}^\top \mathbf{P}_2 &= 0 \end{aligned}$$

⁶see some notes about $\lambda = 0$ in the talk notes

Estimation of the P matrix

$$\begin{aligned} u\mathbf{X}^\top \mathbf{P}_3 - \mathbf{X}^\top \mathbf{P}_1 &= 0 \\ v\mathbf{X}^\top \mathbf{P}_3 - \mathbf{X}^\top \mathbf{P}_2 &= 0 \end{aligned}$$

Re-shuffle into a matrix form:

$$\underbrace{\begin{bmatrix} -\mathbf{X}^\top & \mathbf{0}^\top & u\mathbf{X}^\top \\ \mathbf{0}^\top & -\mathbf{X}^\top & v\mathbf{X}^\top \end{bmatrix}}_{\mathbf{A}_{[2 \times 12]}} \underbrace{\begin{bmatrix} \mathbf{P}_1 \\ \mathbf{P}_2 \\ \mathbf{P}_3 \end{bmatrix}}_{\mathbf{P}_{[12 \times 1]}} = \mathbf{0}_{[2 \times 1]}$$

A correspondence $\mathbf{u}_i \leftrightarrow \mathbf{X}_i$ forms two homogeneous equations. \mathbf{P} has 12 parameters but scale does not matter. We need at least 6 2D \leftrightarrow 3D pairs to get a solution. We constitute $\mathbf{A}_{[\geq 12 \times 12]}$ data matrix and solve

$$\mathbf{p}^* = \operatorname{argmin} \|\mathbf{Ap}\| \text{ subject to } \|\mathbf{p}\| = 1$$

which is a constrained LSQ problem. \mathbf{p}^* minimizes algebraic error

Decomposition of P into the calibration parameters

$$P = \begin{bmatrix} KR & Kt \end{bmatrix} \quad \text{and} \quad C = -R^{-1}t$$

We know that R should be 3×3 orthonormal, and K upper triangular.

```
P = P./norm(P(3,1:3));
```




```
[K,R] = rq(P(:,1:3));
```

```
t = inv(K)*P(:,4);
```


```
C = -R'*t;
```

See the [slide notes](#) for more details.


An example of a calibration object




2D projections localized




Reprojection for linear model



Reprojection for full model



Reprojection errors—comparison between full and linear model



References



The book [2] is the ultimate reference. It is a must read for anyone wanting to use cameras for 3D computing.


Details about matrix decompositions used throughout the lecture can be found at [1]


- [1] Gene H. Golub and Charles F. Van Loan. **Matrix Computation**. Johns Hopkins Studies in the Mathematical Sciences. Johns Hopkins University Press, Baltimore, USA, 3rd edition, 1996.
- [2] Richard Hartley and Andrew Zisserman. **Multiple view geometry in computer vision**. Cambridge University, Cambridge, 2nd edition, 2003.

End


















image plane




$$\frac{x_1}{-f} = \frac{X_1}{Z_1}$$
$$x_1 = -f \frac{X_1}{Z_1}$$















X °


































100

200

300

400

500


600


700


800

900


1000

































sorted 2D reprojection errors

